

TECHNICAL DATA SHEET

Wallshell® Joint Sealant



Properties

Wallshell® joint sealants are silicone weatherproofing sealant which made of Silicone, Carbon black, Methyltrimethoxysilane, Quartz and Titanium dioxide. It caulking sealant for joints among panels.

Composition / Information on Ingredients

Substance Name	% in Weight
Carbon black	1% - 10%
Methyltrimethoxysilane	0.1% - 1%
Quartz	0.1% - 1%
Titanium dioxide	0.1% - 1%

Technical Data

Properties	Average Value
Appearance	Paste
Color	Black
Specific Gravity	1.48
Self-ignition	Not classified as pyrophoric
Oxidizing properties:	Not classified as oxidizing.
Explosive properties	Not explosive

Delivery

Packaging
Box

Storage

Storage Conditions
Dry condition

Application Requirements

Apply Wallshell® Joint Sealant: Thoroughly cover all the cuttings

Special Information

THE INFORMATION OR DATA IN THIS SHEET SERVES TO ENSURE THE PRODUCT'S INTENDED PURPOSE OR ITS SUITABILITY FOR USE AND IS BASED ON OUR FINDINGS AND EXPERIENCE. NEVERTHELESS, USERS ARE RESPONSIBLE FOR ESTABLISHING THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE. APPLICATIONS OTHER THAN THOSE EXPLICITLY MENTIONED IN THIS TECHNICAL DATA SHEET ARE ONLY PERMISSIBLE AFTER PRIOR CONSULTATION WITH WALPANEL, INC. WHERE NO APPROVAL IS GIVEN, SUCH APPLICATIONS ARE AT THE RISK OF THE USER. THIS APPLIES IN PARTICULAR WHEN THE PRODUCT IS USED IN COMBINATION WITH OTHER PRODUCTS. WHEN A NEW TECHNICAL DATA SHEET IS PUBLISHED, ALL PREVIOUS TECHNICAL DATA SHEETS ARE NO LONGER VALID. THE LATEST VERSION IS AVAILABLE ON THE INTERNET AT WWW.WALLSHELL.COM.